

SePem® 351

Technical data sheet

Device data	
Dimensions (H x Ø)	126 x 54 mm (without aerial)
Weight	approx. 760 g (without aerial)

Certificates	
Certificate	CE

Features	
Signal light	1 LED
Memory	128 kB
Processor	microcontroller 16 bit
Ports	<ul style="list-style-type: none"> • TNC port • 3-pin communication contact
Control	Reed switch for testing the radio connection

Operating conditions	
Operating temperature	-20 – 55°C
Storage temperature	-20 – 70 °C
Humidity	100% r.h.
Atmospheric pressure	900 – 1180 hPa
Protection rating	IP68
Permitted operating environments	submersible up to 1 m
Non-permitted operating environments	<ul style="list-style-type: none"> • in liquids other than water • in aggressive media • in potentially explosive areas

Power supply	
Power supply	lithium metal battery [1355-0022]
Lithium mass per cell	2.8 g
Net weight of batteries	61 g
Operating time, typical	9 years when using the default settings

Measurement data recording	
Type	noise sensor
Sampling rate	adjustable 1 s – 1 h
Measuring range	0 – 3000

Data transmission	
Communication	<ul style="list-style-type: none"> • LoRaWAN® • cable
Frequency bands	LoRaWAN® AS923, AU915, EU868, KR920, IN865

Additional data	
Attachment option	magnetically to the measuring location
Shipping instructions	contains: <ul style="list-style-type: none"> • 1 lithium metal battery packed with equipment (UN 3091) • with 2.8 g lithium transport as per ADR class 9 and VA 970 part I IATA possible

Assignment	
System components of	SePem system

LoRaWAN® is a brand used under the LoRa Alliance® licence.
Subject to technical changes.